



Euphoria



Mystical



Passion



Made In The USA



Euphoria



Mystical



Passion



Euphoria Mosaic - Square 2"x2"



Mystical Mosaic - Square 2"x2"



Passion Mosaic - Square 2"x2"



	FLOOR TILE	DECOS	TRIMS*
Thickness	13"x13" (33.3x33.3 cm) 3/8" (10 mm)	20"x20" (50x50 cm) 7/16" (10.8 mm)	13"x13" (33.3x33.3 cm) Mosaic - Square 2"x2" 3"x13" (8x33.3 cm) Bullnose
Names (colors)	AL77	AL7A	AL7D
Euphoria (grey)	AL77	AL7A	AL7D
Mystical (beige)	AL76	AL79	AL7C
Passion (charcoal)	AL78	AL7B	AL7E

Notes: * Trim is available in all colors and made to complement Modular and Floor Tile.

ASTM Test Results

TECHNICAL CHARACTERISTICS	ANSI STANDARD	ASTM TEST RESULTS	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	20"x20" 13"x13"	≥ 250 lbf. ≥ 250 lbf.	C648 C648
Facial Dimension	-3.0 % < Nominal ≤ 3.0 %	Within Standard	C499
Thickness	≤0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm**	Within Standard	C502
Warpage (Flatness)	+/- 0.75% or +/- 2.3 mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV*	C1027
C.O.F. (Wet)	As Reported	0.50 ≤ COF < 0.60	C1028
C.O.F. (Dry)	As Reported	0.80 ≤ COF < 0.90	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Abrasion Resistance / Suggested Applications
Class IV; Tile in this class may withstand heavier amounts of traffic with greater amounts of dirt and/or other abrasives present including commercial kitchens and areas with regular traffic from the outside.
** Whichever is less